

Laminated Plastic Adhesive - LP-Gold

Technical Data Sheet

Rev00, 14 Jan 2019

DESCRIPTION

A golden yellow multipurpose solvent-based synthetic rubber resin adhesive. It has excellent bond strength and high heat resistance. This product is low smell adhesive suitable for multiple uses in the automotive, upholstery, interior furnishing, flooring, wood working and insulation material industries, amongest other. It is high resistance to high temperatures and forms strong bonds between bonded substrate.

APPLICATIONS

Dunlop Laminated Plastic Adhesive-LP-Gold is both brushable and sprayable type. Which is suitable for bonding a porous material such as formica, resopal, veneer strips, MDF, edges, wood, leather, cork, and flexible foam.

SPECIFICATION

APPEARANCE : Viscous Liquid Product

COLOR : Golden Yellow BASE : Polychloroprene

TOTAL SOLID CONTENT : 23 - 25 %

VISCOSITY : 3,500 – 4,500 centipoise
PEEL STRENGTH : 70N/25mm.width.minimum
SPECIFIC GRAVITY : 0.85-0.90 [Ref Std: WATER=1]

DRYING TIME : 7 min. – 1 hrs. THINNER / CLEANER : Dunlop T – 559

HEAT RESISTANCE : 100 C(After heat 1 hour)

HEALTH AND SAFETY

The solvents contained in this product are highly inflammable and subject to legislation regulating their storage and use.

STORAGE AND SHELF LIFE

Store in well sealed containers. Keep satisfactorily for at least 6 months. High temperature storage should be avoided and recommend to store within the temperature 4 to 30 c.