



DAT GP Low VOC

Technical Data Sheet

DESCRIPTION

A golden yellow low volatile organic compound (Low VOC) solvent-based synthetic rubber resin adhesive. It has excellent bond strength and high heat resistance. It has been specially developed for environment friendly for industries. This product is LOW VOC adhesive suitable for multiple uses in the automotive, upholstery, interior furnishing, flooring, wood working and insulation material industries, amongst other. It is high resistance to high temperatures and forms strong bonds between bonded substrate.

APPLICATIONS

DAT GP Low VOC Adhesive is both brushable type. Which is suitable for bonding a porous material such as formica, resopal, veneer strips, MDF, wood, leather, cork, and flexible foam.

SPECIFICATION

APPEARANCE	:	Viscous Liquid Product
COLOR	:	Golden Yellow
BASE	:	Polychloroprene
TOTAL SOLID CONTENT	:	18 - 20 %
VISCOSITY	:	3,500 – 5,500 centipoise
PEEL STRENGTH	:	70N/25mm.width.minimum
SPECIFIC GRAVITY	:	0.85-0.90 [Ref Std: WATER=1]
DRYING TIME	:	7 min. – 1 hrs.

HEALTH AND SAFETY

The solvents contained in this product are highly inflammable and subject to legislation regulating their storage and use.

STORAGE AND SHELF LIFE

Store in well sealed containers. Keep satisfactorily for at least 6 months. High temperature storage should be avoided and recommend to store within the temperature 4 to 30 c.