

Technical Data Sheet

DESCRIPTION

DAT-LP is a premium low smell adhesive recommended for high pressure laminates and suitable for shoe, interior furnishings, leather goods and wood working industries amongst others. It is extremely resistant to high temperatures and forms strong bonds between bonded substrates.



Key materials*	Not Recommended
HPL	Polyethylene (PE)
Wood	Polypropylene (PP)
PU foam flex/rigid	Teflon
Leather and upholstery	Silicone
Rubber	
Other porous material	

**Not limited to*

APPLICATION

The substrates should be clean, dry, free of dust, oil, grease and other contaminants.

Apply DAT-GP to both substrates using brush or trowel and allow the adhesive to dry for 7-25 minutes or until touch dry before applying both substrates together ensuring no air bubbles. Apply even pressure for adhesion.

Any residue can be cleaned with DAT thinners.

PROPERTIES

APPEARANCE	:	Viscous liquid product
COLOR	:	Golden Yellow
BASE	:	Polychloroprene
SOLID CONTENT	:	21-23%
VISCOSITY	:	3500-4500 cps
DRYING TIME	:	7 mins – 30 mins

DAT GP

STORAGE AND SHELF LIFE

Store in well-sealed containers. Keep satisfactorily for at least 12 months. High temperature storage should be avoided and recommend to store within the temperature 4 to 30 c.