



D250 Liquid nails Construction Adhesive

Technical Data Sheet

Rev01, 16 Jan 2019

DESCRIPTION

D250 Liquid Nails Construction Adhesive is a general purpose construction adhesive suitable to variety of building materials. D250 excellent initial bonding strength, high flexibility, high temperature resistance and good slump resistance also can use both of indoor and outdoor.

APPLICATIONS

D250 Liquid Nails Construction Adhesive can use as contact adhesive for variety of building materials such as wall, floor panels, timber, metal and other materials to concrete, plaster or rigid surface, Polystyrene foam without effect with foam, Installation battens to brick, Masonry or concrete wall.

SPECIFICATION

APPEARANCE	:	Thixotropic Paste.
COLOR	:	Beige.
BASE	:	Synthetic Rubber
TOTAL SOLID CONTENT	:	70 - 75 %
SPECIFIC GRAVITY	:	1.10 - 1.15 [<i>Ref Std: WATER=1</i>]
DRYING TIME	:	10 – 30 minutes.
SETTING TIME	:	24 Hrs.

INSTRUCTIONS

The surface must be clean and dried and free from grease, oil and dust

HEALTH AND SAFETY

The solvents contained in this product are highly inflammable and subject to legislation regulating their storage and use.

STORAGE AND SHELF LIFE

Store in cool and place. Avoided direct expose sun light. Keep satisfactorily for at least 3 years. High temperature storage should be avoided and recommend to store within the temperature 4 to 30 c.