



General Purpose Adhesive – GP LS

Technical Data Sheet

Rev05 24Mar2025

DESCRIPTION

This is a high-performance, golden yellow, low-odour, solvent-based synthetic rubber resin adhesive. Specially formulated to minimize solvent fumes, it helps save both time and money for our customers. Ideal for a wide range of applications, including the footwear industry, leather goods, automotive, upholstery, interior furnishings, flooring, woodworking, and insulation industries.

APPLICATIONS

Dunlop General Purpose Adhesive-GP Low Smell is a brushable adhesive, specifically designed for bonding porous materials such as wood, leather, cork, and flexible foam.

SPECIFICATION

Appearance	Viscous Liquid Product
Colour	Golden Yellow
Base	Polychloroprene
Total Solid Content	18 - 20 %
Viscosity	4,000 – 5,000 centipoises
Specific Gravity	0.85-0.90 [<i>Ref Std: WATER=1</i>]
Drying Time	7 min. – 1 hrs
Thinner / Cleaner	Dunlop T - 559

HEALTH AND SAFETY

This product contains highly flammable solvents and is subject to regulations governing their storage and use.

STORAGE AND SHELF LIFE

Store in tightly sealed containers to maintain quality for at least 3 years. Avoid storing at high temperatures; it is recommended to keep the product within a temperature range of 4°C to 30°C.