



Laminated Plastic Adhesive – LP

Technical Data Sheet

Rev05 24Mar 2025

DESCRIPTION

A golden yellow, multipurpose, solvent-based synthetic rubber resin adhesive, offering excellent bond strength and superior heat resistance.

APPLICATIONS

Dunlop Laminated Plastic Adhesive-LP is available in both brushable and sprayable forms. It is ideal for bonding porous materials such as Formica, Resopal, veneer strips, MDF, edges, wood, leather, cork, metal, and flexible foam.

SPECIFICATION

Appearance	Viscous Liquid Product
Colour	Golden Yellow
Base	Polychloroprene
Total Solid Content	23 - 25 %
Viscosity	3,500 – 4,500 centipoises
Peel Strength	70N/25mm.width.minimum
Specific Gravity	0.85-0.90 [Ref Std: WATER=1]
Drying Time	7 min. – 1 hrs.
Thinner / Cleaner	Dunlop T - 559
Heat Resistance	100°C (After heat 1 hour)
Coverage Area (1 side)	9 – 10 m ² /Kg.

HEALTH AND SAFETY

The solvents in this product are highly flammable and are subject to regulations governing their storage and use.

STORAGE AND SHELF LIFE

Store in tightly sealed containers to maintain quality for at least 3 years. Avoid storage at high temperatures and ensure the product is stored within a temperature range of 4°C to 30°C.