



Laminated Plastic Adhesive – LP

Technical Data Sheet

Rev00, 14 Jan 2019

DESCRIPTION

A golden yellow multipurpose solvent-based synthetic rubber resin adhesive. It has excellent bond strength and high heat resistance..

APPLICATIONS

Dunlop Laminated Plastic Adhesive-LP is both brushable and sprayable type. Which is suitable for bonding a porous material such as formica, resopal, veneer strips, MDF, edges, wood, leather, cork, metal and flexible foam.

SPECIFICATION

APPEARANCE	:	Viscous Liquid Product
COLOR	:	Golden Yellow
BASE	:	Polychloroprene
TOTAL SOLID CONTENT	:	23 - 25 %
VISCOSITY	:	3,500 – 4,500 centipoise
PEEL STRENGTH	:	70N/25mm.width.minimum
SPECIFIC GRAVITY	:	0.85-0.90 [Ref Std: WATER=1]
DRYING TIME	:	7 min. – 1 hrs.
THINNER / CLEANER	:	Dunlop T – 559
HEAT RESISTANCE	:	100 C(After heat 1 hour)

HEALTH AND SAFETY

The solvents contained in this product are highly inflammable and subject to legislation regulating their storage and use.

STORAGE AND SHELF LIFE

Store in well sealed containers. Keep satisfactorily for at least 6 months. High temperature storage should be avoided and recommend to store within the temperature 4 to 30 c.