



## **D125 ALL WEATHER SEALANT**

## **Technical Data Sheet**

Rev.00, 16 Feb 2021

### **DESCRIPTION**

DUNLOP D125 All Weather Sealant is a flexible, elastic one-component acrylic dispersion based sealant which is reinforced with silicone emulsion; forming a permanent water repellent layer after curing making it resistant to weather conditions.

### **Properties**

- Easy application
- Paintable
- Does not affect the application surface
- Bright, glossy appearance
- Can be used for all porous surfaces
- Water, wind and moisture resistant on aluminium, wood, and PVC frames & windows.

### **SPECIFICATION**

APPEARANCE	:	Cartridge.
COLOR	:	White.
BASE	:	Acrylic
DENSITY	:	1.55 g/cm <sup>3</sup>
TACK FREE TIME	:	15 – 45 mins.
CURE RATE	:	2.0 mm/24hrs.
VOLUME SHINKAGE	:	30 %
WEIGHT LOSS	:	20 %
TENSILE STRENGTH	:	>0.1 Mpa

### **INSTRUCTIONS**

Ideal for joint between prefabricate construction element; assembly of wood, PVC, iron and aluminium joinery; joints in stone, wood, concrete, plaster and brick work and sealing of window and door frames to masonry.

### **STORAGE AND SHELF LIFE**

Store in a cool dry place, away from direct sunlight and sources of heat ignition.  
Store at temperatures between +5°C and +25°C