

PRODUCT DESCRIPTION

DAT ACRV3 is the professional solution to installing vinyl flooring and wall coverings in commercial, retail and DIY projects. DAT ACR-V3 is PSA type and has an extended working time and high resistance to plasticiser migration.

APPLICATIONS

DAT ACR-V3 comes ready mixed (1 component) and should be applied by trowel directly to the substrate (concrete, sand/cement screeds, chipboard, hardboard, plywood). The adhesive must be allowed to dry and become clear before applying floor coverings.

Ideal for commercial areas, hospitals, sports facilities, hospitals, schools, and residential and domestic uses.

PRODUCT CHARACTERISTICS

Appearance	Viscous Paste
Colour	Off White/dries clear
Base	Acrylic Polymer
Solid Content	60-65%
Viscosity	25,000 – 30,000
Coverage	Up to 5m ² / kg
Working Time	2 hours+

STORAGE AND SHELF LIFE

Store in well-sealed containers. Keep satisfactorily for at least 1 year unopened. High temperature storage should be avoided and it is recommended to store within the temperature 4 to 30c and out of direct sunlight.

Once open consume within 6 months.



KEY BENEFITS

- ✓ Anti Fungal
- ✓ Low VOC
- ✓ Long Working Time

PRIMARY SUBSTRATES

- ✓ PVC Sheet Vinyl
- ✓ LVT
- ✓ Vinyl Tiles
- ✓ PVC backed carpets
- ✓ Linoleum
- ✓ Rubber Flooring
- ✓ Carpet tiles

CAUTION: Despite Dunlop Adhesives' belief that the statements and technical information in this document are reliable based on tests or data, it does not warrant or guarantee their accuracy or completeness. The user is solely responsible for controlling factors that may impact the performance of Dunlop Adhesives' products in their intended application. This includes conducting tests to determine the compatibility of the product with the design, structure, and materials of the end product, as well as verifying the suitability of the product for the user's method of application and intended use. The user must assume all risk and liability associated with using the product in question.



PREPARATION






1. Ensure the subfloor is clean, dry and free from dust, grit, oil and grease.
2. The subfloor should be tested to relevant standards to ensure that it is appropriately dry.
3. Any areas of the subfloor in need of localised repairs should be patched up to achieve a smooth and level base.
4. Subfloors with high porosity should be primed prior to applying adhesive and allowed to fully dry.

APPLICATION DATA

Application temp	18°C - 24°C
Coverage	Up to 100m ² per 20kg (depending on trowel, floor smoothness and application)
Open/Working Time	60/120 minutes+ (depending on ambient conditions)
Drying Time	Foot traffic after 24 hours (depending on ambient conditions)
Cleaning	Clean tools with warm water immediately after use

MATERIAL


TROWEL SIZE

PVC sheet and tile	A1	
LVT	A2	
Linoleum	A1	
Rubber	A1	
Carpet	A1	

METHOD GUIDE

PSA

Evenly trowel adhesive out on to the subfloor. The adhesive must be allowed to completely dry and become clear before applying floor coverings. After application, use a roller to apply even pressure, ensuring full contact between the adhesive and the flooring.



- **Open Time:** The minimum time the adhesive should be left exposed to air after being troweled onto the subfloor.
- **Working Time:** The recommended window after the open time during which the floor covering should be installed.

Ensure installation is completed in manageable sections, keeping these times in consideration.

CAUTION: Despite Dunlop Adhesives' belief that the statements and technical information in this document are reliable based on tests or data, it does not warrant or guarantee their accuracy or completeness. The user is solely responsible for controlling factors that may impact the performance of Dunlop Adhesives' products in their intended application. This includes conducting tests to determine the compatibility of the product with the design, structure, and materials of the end product, as well as verifying the suitability of the product for the user's method of application and intended use. The user must assume all risk and liability associated with using the product in question.

